

**SCHEDA TECNICA****BOFA AD ACCESS - LIGHT DUTY LASER MARKING****Technical data**

Noise level	< 61dBA (at typical operating speed)	< 56dBA (at typical operating speed)
Weight	24kg	52.8lbs
Approvals	CE	cUL, UL

DeepPleat pre filter specifications

Surface media area	1.74m ² approx (18.7 ft ²)
Filter media	Glass fibre
Filter media construction	50mm maxi fold construction with webbing spacers (0.16ft)
Filter efficiency	95% @ 0.9 microns

Combined filter specifications

HEPA filter media	Glass fibre
HEPA media construction	Maxi fold construction with webbing spacers
Filter housing	Zintec mild steel
Treated activated carbon	7 Kgs approx (15.4 lbs)
Filter efficiency	99.997% @ 0.3 microns

Part numbers

Model	Voltage	Part no.	24V Stop / Start	Filter change / System failure signal	VOC monitoring	Hose kit
AD Access Stainless steel	230V	L1852A	A2001	A2002	A2003	A1020007
AD Access Powder coated	230V	L1842A	A2001	A2002	A2003	A1020007
AD Access Powder coated	115V	L1841A	A2001	A2002	A2003	A1020007

Replacement filters

Model	DeepPleat pre filter	Combined HEPA / Gas filter
AD Access	A1030153	A1030154